

# UNIVERSAL PNEUMATIC SHOCK ABSORBER DISMANTLER



## 447 T

2006/42/CE

**PROMO**

- Ideal for cars
- Self-levelling system of the two upper arms: also fits into conical and disaligned springs
- Self-lubricating: no lubrication and/or greasing necessary on the sliding columns
- Supplied with lower brackets 447 TC1 (78÷130 mm) and 447 TC2 (105÷182 mm), vice 447 TA and universal upper clamps 447 TB1
- Compact dimensions for easy installation in the shop 470x450x1390 mm
- Complies with MACHINE DIRECTIVE 2006/42/CE

Compression power 735 kg (6 bar), 1226 kg (10 bar)

Cylinder Lega di alluminio e resina al nylon

Piston stroke (mm) 420

Recommended air pressure (bar) 6÷10

Lower brackets/vice Aggancio/sgancio rapido

## Family details

Code	LxPxH mm	Weight kg	Quantity for packaging
U04470101	470x450x1390	60	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000