

ALUMINIUM IMPACT WRENCH



910 E1 1

- Reversible model with double hammer mechanism
- Four power settings for tightening and untightening
- Spare rotor blades (6 pieces): code 31K100061

Square drive (")	1
Strokes per minute	720
Vibrations (m/s ²)	15,20
Average air consumption (l/min)	243
Sound power dB(A)	113 ±3
Torque range (Nm)	850÷1300
Free speed (rpm)	4500
Ø hose size (mm)	13
Sound level dB(A)	102 ±3
Max torque (Nm)	4068
Air inlet (")	1/2
Recommended air pressure (bar)	6,2
Bolt capacity	M33

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Family details

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U09100020	300x205x290	10,3	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000