

ALUMINIUM IMPACT WRENCH

928 D1
3/4



- Reversible model with double hammer mechanism
- Six power settings for tightening and untightening
- Spare rotor blades (6 pieces): code 31K100021

Square drive (")	3/4
Strokes per minute	790
Air inlet (")	3/8
Recommended air pressure (bar)	6,2
Torque in use (Nm min-Max)	500÷1050
Vibrations (m/s ²)	9,1
Average air consumption (l/min)	193
Sound power dB(A)	109,4 ±3
Max torque (Nm)	1700
Free speed (rpm)	5700
Ø hose size (mm)	13

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Sound level dB(A)	98,4 ±3
-------------------	---------

Bolt capacity	M24
---------------	-----

Family details

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U09280015	222x93x233	5,6	1

Sets / Compositons

Articles



[928 DN/S12 - Assortment with impact wrench in sheet steel case \(13 pcs.\)](#)

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Le informazioni e le immagini qui contenute sono soggette a continuo aggiornamento: tali dati sono pertanto da ritenersi indicativi e suscettibili di eventuali errori e/o imprecisioni.
Stanley Black & Decker Italia S.r.l. declina ogni responsabilità circa le informazioni e le indicazioni ivi contenute.