

AUTOMOTIVE DIGITAL MULTIMETER



076 F

- Measures voltage and current AC/DC, resistance, capacity, temperature
- Continuity and diodes test
- Automatic calibration function
- Data hold
- Duty cycle indication
- Dwell angle/rpm
- Supplied with a pair of insulated tips for battery and thermocouple
- Spare parts (not included in the package):
Kit fuses (2 pieces): 711A-F
Spare tips (2 pieces): 711A-L
- CAT III 600 V

Direct voltage DC (mV÷V)	400÷600
Response in frequency Hz	40÷400
Resistance (Ω÷MΩ)	400÷40
Alternating current AC (μA÷mA)	400÷400
DWELL	180° (2 cil) ÷ 45° (8 cil)
Direct current DC (μA÷mA)	400÷400
Temperature with K probe	-20°C÷1000°C
Overload protection DC/AC (V)	600
Alternating voltage AC (V÷V)	4÷600
Battery type (supplied)	6xAAA
Measurement RPM	250÷40000

Family details

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000



Code

 Weight gr

 Quantity for packaging

U00760004

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000