

90° ANGLE GRINDER - 0.3 CV (220 W)

922 BP1

PROMO



- Model with head angled at 90°
- It can be used for removing weld lines and burrs, for grinding welded areas,

of sanding, deburring, finishing, cutting, etc.

- Double internal bearing system to ensure a longer tool life
- Body and handle in resistant antislip material insulated against cold and vibrations
- Adjustable speed- Snap safety lever
- Supplied with 6 mm collet- Rear air exhaust- Spare rotor blades (4 pieces): code N444798
- Spare collet 6 mm: code N444782

| | |
|---------------------------------|---------|
| Recommended air pressure (bar) | 6,2 |
| Free speed (rpm) | 23000 |
| Air inlet (") | 1/4 |
| Average air consumption (l/min) | 76 |
| Vibrations (m/s ²) | 4,54 |
| Sound power dB(A) | 96,9 ±3 |
| Collet size (mm) | 6 |
| Power (CV-W) | 0,3-220 |
| Ø hose size (mm) | 10 |
| Sound level dB(A) | 85,9 ±3 |

Family details

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

| Code | LxPxH mm |  Weight gr |  Quantity for packaging |
|-----------|-----------|---|--|
| U09220004 | 165x27x75 | 555 | 1 |

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

*Le informazioni e le immagini qui contenute sono soggette a continuo aggiornamento: tali dati sono pertanto da ritenersi indicativi e suscettibili di eventuali errori e/o imprecisioni.
Stanley Black & Decker Italia S.r.l. declina ogni responsabilità circa le informazioni e le indicazioni ivi contenute.*