

## IMPACT WRENCH (COMPOSITE MATERIAL FRAME)



### 942 PE1 1

#### PROMO

- Lightweight and balanced for easy use, only 6.8 Kg
- Reversible model with double hammer - Progressive trigger
- Air exhaust through the handle
- 2 tightening torque settings, always maximum untightening power
- Soft-touch bimaterial grip
- Additional soft-touch bimaterial handle allows strong and firm grip
- Socket retaining system on square drive with holding ring and hole to be used with lock pin and safety ring
- Spare rotor blades (6 pieces): code 30M200147

Square drive (")	1
Strokes per minute	900
Air inlet (")	1/2
Recommended air pressure (bar)	6,2
Torque in use (Nm min-Max)	203÷1627
Vibrations (m/s <sup>2</sup> )	10,6
Average air consumption (l/min)	440
Sound power dB(A)	111,9 ±3
Max torque (Nm)	3390
Free speed (rpm)	5000
Ø hose size (mm)	19
Sound level dB(A)	100,9 ±3

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**



Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000

---

Bolt capacity

M38

## Family details

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U09420005	243x96x249	6,8	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo  
da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000