

IMPACT WRENCH (COMPOSITE MATERIAL FRAME)



942 PE1 1

- Lightweight and balanced for easy use, only 6.8 Kg
- Reversible model with double hammer
- Progressive trigger
- Air exhaust through the handle
- 2 tightening torque settings, always maximum untightening power
- Soft-touch bimaterial grip
- Additional soft-touch bimaterial handle allows strong and firm grip
- Socket retaining system on square drive with holding ring and hole to be used with lock pin and safety ring
- Spare rotor blades (6 pieces): code 30M200147

Strokes per minute	900
Square drive (")	1
Air inlet (")	1/2
Recommended air pressure (bar)	6,2
Torque in use (Nm min-Max)	203÷1627
Average air consumption (l/min)	440
Vibrations (m/s ²)	10,6
Sound power dB(A)	111,9 ±3
Max torque (Nm)	3390
Free speed (rpm)	5000
Sound level dB(A)	100,9 ±3

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000



Ø hose size (mm)	19
------------------	----

Bolt capacity	M38
---------------	-----

Family details

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U09420005	243x96x249	6,8	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000