

REVERSIBLE STRAIGHT IMPACT WRENCH WITH LONG ANVIL (COMPOSITE MATERIAL FRAME)

942 PEL2 1



- Lightweight and balanced for easy use, only 9 Kg
- Reversible model with double hammer
- Long-reach anvil for access in hard to reach areas
- Progressive trigger
- Air exhaust through the handle, at 45°
- 2 tightening torque settings, always maximum untightening power
- Soft-touch bimaterial grip
- Additional soft-touch bimaterial handle allows strong and firm grip
- Socket retaining system on square drive with holding ring and hole to be used with lock pin and safety ring
- Spare rotor blades (6 pieces): code 30M100147

Square drive (")	1
Free speed (rpm)	5000
Sound power dB(A)	116 ±3
Ø hose size (mm)	19
Sound level dB(A)	105 ±3
Air inlet (")	1/2
Recommended air pressure (bar)	6,2
Strokes per minute	1000
Torque in use (Nm min-Max)	203÷1627
Vibrations (m/s ²)	15,6

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Average air consumption (l/min)	480
---------------------------------	-----

Max torque (Nm)	3390
-----------------	------

Family details

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U09420010	493x97x101	9	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000