

SINGLE ENDED OPEN JAW WRENCHES - 1000 V

099 A

ISO 4429 EN 60900



- Bimaterial layered insulation with ergonomic grip surface
- The insulation is in critical condition when the yellow layer becomes visible.
- Each one is tested according to the European standard EN 60900 to ensure safe work

Family details

Code	 Hexagonal opening mm	L mm	 Weight gr	 Quantity for packaging
U00990108	8	105	30	1
U00990109	9	105	35	1
U00990110	10	105	40	1
U00990111	11	115	50	1
U00990112	12	125	60	1
U00990113	13	135	70	1
U00990114	14	145	80	1
U00990115	15	145	90	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Code	 Hexagonal opening mm	L mm	 Weight gr	 Quantity for packaging
U00990116	16	155	105	1
U00990117	17	155	120	1
U00990118	18	160	135	1
U00990119	19	165	150	1
U00990121	21	185	180	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000