

ALUMINIUM IMPACT WRENCH



928 AC1 1/2

- Steel front casing
- Aluminum motor housing
- Reversible model with double hammer mechanism
- 7 torque settings, in both directions of rotation
- Progressive trigger
- Soft-touch bi-material handle
- Silencer and air exhaust integrated in the handle
- Spare rotor blades (6 pieces): code N573357

Square drive (")	1/2
Strokes per minute	1120
Recommended air pressure (bar)	6,2
Air inlet (")	1/4
Torque in use (Nm min-Max)	135÷380
Average air consumption (l/min)	147
Vibrations (m/s ²)	5,2
Sound power dB(A)	101 ±3
Max torque (Nm)	1490
Free speed (rpm)	6500
Sound level dB(A)	90 ±3
Ø internal hose (mm)	10

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138



StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Bolt capacity

M16

Family details

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U09280014	190x70x193	2,8	1

Sets / Compositons

Articles



928 A1/S3 - Counter display stand with impact wrenches

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
 Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
 Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
 Capitale Sociale I.V. € 12.000.000