

LED TORCH IN ALUMINIUM - 680 LUMEN

889 TL



- Anodised Aluminium body
- Built-in front glass
- 3 lighting modes: high-medium-strobe
- Adjustable zoom function
- Switch on with back button

Light source	1 x SMD LED
Autonomy min-max (hours)	6-15
Battery type (not supplied)	3 x C
Protection level	IP54
Light beam distance (m)	250
Working temperature (°C)	-20 ÷ +50
Color temperature (k)	7500
Light flux (lm)	680-190-Strobo
N° lighting modes	3

Family details

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Code	LxPxH mm	 Weight gr	 Quantity for packaging
U08890072	213x40x31	210	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000