

SPECIAL TUNGSTEN CARBIDE TIPS (2 PCS.)

272 P



- Diameter Ø 8,7 mm
- Clockwise rotation
- Adjustable stop ring for millimeter precise drilling depth
- To be used only with a drill without impact
- Do not exceed 750 rpm to safeguard the tip life
- During use, it is recommended to refrigerate with cutting oil

Family details

Code	Ø mm	L mm	 Quantity for packaging
U02720002	8,7	121	1

Sets / Compositons

Articles



[272 DS - Kit to extract nuts and screws from alloy wheels \(10 pcs.\)](#)

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Articles



[519 M 272DS - Bi-colour foam module with assortment \(10 pcs.\)](#)

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000