

PROFESSIONAL START BOOSTER 12-24 V, PORTABLE



1613 AGM12-24

- For emergency starting
- For intensive professional use
- Ideal for cars, vans, trucks, boats, vehicles agricultural, generators etc.
- Voltmeter to indicate the charge status of the internal battery
- Rear connector for voltage selection
- External fuse: overcurrent protection up to 300A
- Shockproof ABS shell
- Overvoltage protection
- Also suitable for sealed batteries
- Inclined clamps
- Supplied with mains charger

Working voltage (V)	12-24
Cable section (mm ²)	35
Cable length (cm)	155
Charging voltage (V)	220-240V AC
Working current 24V (A)	700
Working current 12V (A)	1400
Battery type (supplied)	2 x AGM 12V
Starting current 24V (A)	1860
Starting current 12V (A)	3700

Family details

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Code	LxPxH mm	 Weight kg	 Quantity for packaging
U16130013	560x590x200	20,8	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000