

LED INSPECTION LAMP



889 RL

- Dual use: inspection lamp or torch
- Magnetic base adjustable up to 180°
- Two rear magnets
- Two retractable hooks that can be rotated 360 °
- 4 LED battery indicator
- Mountable on tripod
- Supplied with USB

Autonomy: torch function (hours)	25
Light source (lamp function)	1 x COB LED (4 W)
Autonomy: lamp function (hours)	3-10
Battery type (supplied)	3.7 V Li-Ion 4400 mAh
Color temperature (k)	5500÷7500K
Color Rendering Index (CRI)	80
Light flux torch (lm)	50
Battery charger (OUTPUT)	DC 5.0V 1A
Light flux lamp (lm)	120-420
Battery charger (INPUT)	AC 100-240V 50/60HZ 0.2A
Shock resistance	IK07
Working temperature (°C)	-20 ÷ +40
Protection level	IP43

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Light intensity torch (lux@0,5m)	800
Beam angle torch	20° ±20%
Beam angle lamp	120° ±20%
Light intensity lamp (lux@0,5m)	80-280
Recharge time (hours)	4,5
Light source (torch function)	1 x SMD LED (0.7 W)

Family details

Code	LxP mm	 Weight gr	 Quantity for packaging
U08890036	215x27	291	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000