

ARTICULATED LED INSPECTION LAMP



889 IL

- Ideal for illuminating narrow points with limited access
- Body in composite material (black part aluminum - red part polypropylene)
- The torch function is activated by holding down the power button for 2 seconds
- 3 lighting modes: head, front, flashlight
- 4-LED battery level indicator (LEDs flash while charging)
- Jointed and 180° adjustable
- Magnet at the end of the headlamp, to retrieve small metal parts
- Magnetic base and hook clamp
- Supplied with USB-C cable

Battery charger (OUTPUT)	DC 5.0V 1A
Light source (lamp function)	1 x COB LED (3.1 W)
Battery charger (INPUT)	AC 100-240V 50/60HZ 0.2A
Recharge time (hours)	4
Color temperature (k)	5500÷7500
Beam angle: lamp-head-torch	120°-120°-40° ±20%
Color Rendering Index lamp-head-torch (CRI)	80-80-70
Light flux: lamp-head-torch (lm)	400-50-150
Autonomy lamp-head-torch (h)	3-35-10
Battery type (supplied)	3.7V Li-ion 2600mAh
Shock resistance	IK07

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Light intensity: lamp-head-torch (lux@0,5m)	420-2300-150
Light source (torch function)	1 x SMD LED (0.5 W)
Protection level	IP20
Light source (head)	1 x SMD LED (1.8 W)

Family details

Code	L max mm	L min mm	P mm	 Quantity for packaging
U08890046	275	160	40	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000