

# LED COMPACT SPOTLIGHT

## 889 GR

- Ideal for illuminating wide working areas
- Super compact
- Body in composite material
- Impact resistant
- Equipped with motion detection sensor: once lamp is turned on, it will be possible to activate the sensor by pressing the button with "hand" logo; If no movements around, after about 20 seconds the lamp will turn off and activating again whenever a movement will be detected (up to 5 meters away)
- Fluorescent reflector to locate the unlit spotlight in very dark areas
- 3 selectable brightness levels
- High resistance reinforced structure
- Magnetic base adjustable in several positions up to 90°
- Adjustable hook up to 360°



Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000

- Mountable on tripod
- Check of charge status with warning light on lamp body (red: charging in progress, green: charge complete)
- Supplied with USB-C cable

|                             |                          |
|-----------------------------|--------------------------|
| Light source                | 18 x 0.5W SMD LED        |
| Operating temperature (°C)  | 0-40                     |
| Recharge time (hours)       | 2,5                      |
| Color temperature (k)       | 5500÷7000                |
| Color Rendering Index (CRI) | 80                       |
| Beam angle                  | 120° ±20%                |
| Light beam distance (m)     | 8-18-25                  |
| Autonomy min-max (hours)    | 18-3,6-1,8               |
| Battery type (supplied)     | 3.7V Li-ion 2600mAh      |
| Shock resistance            | IK07                     |
| Battery charger (OUTPUT)    | DC 5.0V 1A               |
| Battery charger (INPUT)     | AC 100-240V 50/60HZ 0.2A |
| Light flux (lm)             | 50-250-500               |
| Light intensity (lux@0,5m)  | 80-360-720               |
| Protection level            | IP54                     |
| N° lighting modes           | 3                        |

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
 Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
 Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
 Capitale Sociale I.V. € 12.000.000

## Family details

| Code      | LxPxH mm |  Weight gr |  Quantity for packaging |
|-----------|----------|---------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| U08890044 | 91x55x47 | 286                                                                                         | 1                                                                                                        |

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo  
da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000