

## LED MINI PENLIGHT



### 889 SP

**NEW!** **PROMO**

- Magnetic hanging clip, 360° adjustable
- Body in composite material (black part aluminum red part polypropylene)
- 2 lighting modes: front and torch
- Check of charge status with warning light on lamp body (red: charging in progress, green: charge complete)
- Supplied with USB-C cable

Light source (lamp function)	1 x 1.3W COB LED
Autonomy lamp (h)	1,5-3
Battery type (supplied)	3.7V Li-Ion 600 mAh
Battery charger (OUTPUT)	DC 5.0V 1A
Color Rendering Index torch (CRI)	70
Light beam distance: torch (m)	70
Light beam distance: lamp (m)	10-15
Color Rendering Index lamp (CRI)	80
Light flux torch (lm)	150
Light flux lamp (lm)	75-150
Battery charger (INPUT)	AC 110-240V 50/60Hz 0.2A
Working temperature (°C)	0-40

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000

Recharge time (hours)	2
Beam angle torch	15°
Beam angle lamp	60°
Autonomy torch (h)	3
Light intensity torch (lux@02m)	315
Color temperature torch (k)	5700-6500
Light intensity lamp (lux@2m)	7-15
Color temperature lamp (k)	5500-6500
Light source (torch function)	1 x 2.2W COB LED

## Family details

Code	LxP mm	 Weight gr	 Quantity for packaging
U08890055	94x20	45	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
 Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
 Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
 Capitale Sociale I.V. € 12.000.000