

DIGITAL MULTIMETER WITH TRUE RMS READING

076 M



- Detectable parameters: AC/DC voltage and current, resistance, continuity, diode test, capacitance, frequency, duty cycle, temperature, DWELL, engine speed, pulse width
- Data hold mode on display
- Relative mode
- Automatic shutdown
- Auto-calibration
- Data storage
- Supplied with a pair of test leads, thermocouple, and 2 AAA batteries
- CAT III 600 V

Direct voltage DC (mV÷V)	6÷600
Resistance (Ω ÷M Ω)	600÷60
Measurement RPM	60÷20.000
Battery type (supplied)	2xAAA
Response in frequency (Hz÷MHz)	9,999÷9,999
Alternating current AC (mA÷A)	60÷10
Direct current DC (mA÷A)	60÷10
DWELL	90° (2 cil)÷45° (8 cil)
Temperature with K probe	-20°C÷1000°C
Alternating voltage AC (mV÷V)	600÷600
Overload protection DC/AC (V)	600

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Family details

Code	 Weight gr
------	---

U00760007	224
-----------	-----

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000