

## AMMETER AND DIGITAL MULTIMETER TRUE RMS

### 076 MC



- Detectable parameters: AC/DC voltage and current, resistance, continuity, diode test, temperature, capacitance, duty cycle, and frequency
- Data hold mode on display
- Min/Max recording mode
- Backlit LCD display
- Low battery indication
- Negative polarity indication
- Overrange indication
- Automatic shutdown
- Low battery indication
- Data storage
- Supplied with a pair of test leads, thermocouple, and 3 AAA batteries
- CAT III 600 V

Operating temperature (°C)	-20÷1000
Direct voltage DC (mV÷V)	0÷600
Resistance (Ω÷MΩ)	0÷60
Alternating current AC (mA÷A)	0÷600
Direct current DC (mA÷A)	0÷600
Capacity (nF÷μF)	6÷60
Battery type (supplied)	3xAAA
Alternating voltage AC (mV÷V)	0÷600
Response in frequency (Hz÷MHz)	1÷9,99

### Family details

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
 Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
 Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.  
 Capitale Sociale I.V. € 12.000.000

Code	 Weight gr	 Quantity for packaging
U00760008	264	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)  
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia  
Partita IVA e C.F.: 03225990138

**StanleyBlack&Decker**

Società a Socio Unico soggetta a coord. e controllo  
da parte di Stanley Black & Decker, Inc.  
Capitale Sociale I.V. € 12.000.000