

FLEXIBLE LED INSPECTION LAMP



889 CM

- Ideal for illuminating tight and hard-to-access areas
- Aluminum handle, torch made of composite material
- 2 lighting modes: front and torch
- Backlit on/off button
- Flexible and 360° adjustable
- Length of flexible cable (including torch): 405 mm
- Magnetic base
- Supplied with USB-C cable

Light source (lamp function)	1 x COB LED (1.8 W)
Battery charger (INPUT)	AC 100-240V 50/60HZ 0.2A
Recharge time (hours)	4
Autonomy: lamp-torch (hours)	9-5
Color Rendering Index torch (CRI)	≥ 80
Color Rendering Index lamp (CRI)	≥ 70
Autonomy lamp (h)	10-5
Light flux torch (lm)	130-250
Light flux lamp (lm)	150-250
Battery type (supplied)	3.7V Li-ion 2600mAh
Color temperature (k)	5500K - 7500K

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000

Le informazioni e le immagini qui contenute sono soggette a continuo aggiornamento: tali dati sono pertanto da ritenersi indicativi e suscettibili di eventuali errori e/o imprecisioni. Stanley Black & Decker Italia S.r.l. declina ogni responsabilità circa le informazioni e le indicazioni ivi contenute.

Battery charger (OUTPUT)	DC 5.0V 1A
Light intensity torch (lux@02m)	10/20
Beam angle torch	12° ±15%
Light intensity lamp (lux@2m)	200/350
Beam angle lamp	65° ±15%
Light source (torch function)	1 x SMD LED (0.5 W)

Family details

Code	L m	 Weight gr	 Quantity for packaging
U08890048	550	280	1

Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB)
Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia
Partita IVA e C.F.: 03225990138

StanleyBlack&Decker

Società a Socio Unico soggetta a coord. e controllo
da parte di Stanley Black & Decker, Inc.
Capitale Sociale I.V. € 12.000.000