



## 890 N

## NEW! PROMO

- Allows testing of the battery health, starting system, and charging system
- Usable with 12V batteries, with capacity 100-2000 CCA, BCI, CA, MCA, IT, SAE; 100-1400 DIN, IEC; JIS 26A17-245H2
- Enables testing of standard (Lead-acid),GEL, EFB, Flat AGM, Spiral AGM, Lithium batteries
- Backlit screen
- Cable length (including clamps): 94 cm
- Reverse polarity protection
- 8 selectable languages: Italian, English, German, French, Dutch, Russian, Spanish, and Portuguese
- Battery can be tested both onboard and off the vehicle
- The tester provides 99.5% accurate results

## **Family details**

Code	LxPxH mm	🛔 Weight gr	Quantity for packaging
U08900002	82x21x131	210	1

## Stanley Black & Decker Italia S.r.l.

Sede legale: Via Energy Park 6 - 20871 Vimercate (MB) Sede operativa: Via Volta 3 - 21020 Monvalle (VA) Italia Partita IVA e C.F: 03225990138



Società a Socio Unico soggetta a coord. e controllo da parte di Stanley Black & Decker, Inc. Capitale Sociale I.V. € 12.000.000

Le informazioni e le immagini qui contenute sono soggette a continuo aggiornamento: tali dati sono pertanto da ritenersi indicativi e suscettibili di eventuali errori e/o imprecisioni. Stanley Black & Decker Italia S.r.I. declina ogni responsabilità circa le informazioni e le indicazioni ivi contenute.